ONE STOP SHOWROOM FOR HOSPITAL & HEALTHCARE PRODUCTS.



FETAL DOPPLER

USER MANUAL - 2019



Email : info@westernsurgical.in Ph. : +91-281-2232871 / 2243159



INDEX
Introduction
Specification
The Product's Structure Composition and Scope of Application

opcomodiion.	
The Product's	s Structure, Composition and Scope of Application
Equipment (Components

How to Use this Doppler.....8

Shelf-life and Warranty......14

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. * Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in Email : westernsurgical@gmail.com Ph. : +91-281-2232871 / 2243159

products. Please read this operation manual before using. In order to consult it next time, please take care of it. Fill the guarantee card and sent it to the agent or the after service department of the headquarters company to confirm your right of free maintenance. If you neither fill the guarantee card nor send it to our company, we will consider that you give up your right automatically, but you will accept the servicing for whole using life all the same. Note: 1.If there is any technical improvement,

Thanks for purchasing our company's

without further notice. 2.Do not privately disassemble. If necessary, operation

and maintenance must be done by a company authorized and qualified technical personnel.

ERN SURGICAL



www.westernsurgical.in Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.

I. Introduction:

- Doppler Fetal Heart Rate (FHR) Detectors apply the ultrasonic Doppler principle to detect the fetal heart beat. The units are compact, lightweight, easy to operate with stable performance and high dependability. has dormancy, LCD display / 2. FETAL DOPPLER
- alarm / self-detect function If there is no signal more than 1 minute, it will switch to

dormancy mode to sea power.

- The blue backlight LCD display makes it possible that the FHR can be seen clearly irrespective of the light is bright or dark, without affecting the detection of heart beat.
- indication/volume indication/alarm of abnormal FHR indication.

All information can be displayed on the LCD,

including the charging mode/residual power

- Self-detect mode ensures the unit to wor normally.
- 3. FETAL DOPPLER can hear the FHR, no display function.

Notes:The content of the tag"*"don't need a referenle.



Due to constant upgradation design, price and features are subject to change any time without prior notice.

WESTERN SURGICAL

6. Optional accessories: earphone and gel.
II. Specification:
Standard: EN61266:1995
Safety Classification: BF (Class II) / Internal

sensitivity 200mm away from the surface of the probe).

frequency is (300 ± 50) Hz, target speed is 10cm / s \sim

No narrower than 65bpm-240bpm (± 2bpm). (Beat Per

While measuring integrated sensitivity, the Doppler

4. This Doppler has **Ni-MH** rechargeable battery inside,

5. Normative collocation: unit, charger, gallus and operation

gallus can make it convenient to carry.

manual.

power.

which can be used repeatedly after recharging. The

40cm / s .Target velocity and display range :

Overall sensitivity: ≥ 90 dB (Integrated

Minute).Alarm range: <120bpm or >160bpm

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.

* Due to constant upgradation design, price and features are subject to change any time without prior notice.

* Www.westernsurgical.in

Email: westernsurgical@gmail.com

Spatial-peak temp-peak acoustic pressure:≤ 0.1 MPa.
 Effective area of transducer:6.0±0.5 cm²
 Adapter input voltage: 230V AC

(Please Visit a doctor once the FHR is abnormal)

Adapter output voltage (no load) : DC12V± 1V

Adapter input consumer(recharging) : ≤ 5VA

Battery : 8.4V Ni-MH batteriesAudio output power : ≤1.8 W

Output power : ≤10Mw/cm²

EMC testing data (See annex II)

Working frequency: 2.0 MHz ± 10%

- Coupling medium impedance: 1.5-1.6 (105g/cm².s)
- Doppler frequency: 0-3.0 KHz
- Working time (after changed):FETAL DOPPLER ≥2hours;
- Working environment: temperature: +5 °C ~ +40 °C
 - Humidity: ≤ 80% Atmospheric pressure: 86kPa ~ 106kPa
 - ~ +40 °C Humidity: ≤ 80%

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.
* Due to constant upgradation design, price and features are subject to change any time without prior notice.



WESTERN SURGICAL www.westernsurgical.in
Email: westernsurgical@gmail.com

Transport and storage environment: temperature: -10 ℃

a) the peak negative acoustic pressure (p_) <1Mpa;b) the output beam of sound intensity(lob) <20mW/cm2;

c) spatial peak time average educed the sound

Atmospheric pressure:86kPa ~ 106kPa,

Acoustic output parameters meet the

meet the following requirements:

intensity (Ispta) <100mW/cm2.

nickel-hydrogen batteries.

well-ventilated room without corrosive gases.

national exempted conditions released that the

ultrasonic and main unit in all operated mode can

- III. The Product's Structure, Composition and
- Scope of Application

 1. Product's structure and composition: mainly by the host,

 Doppler ultrasound transducer and rechargeable
- Product scope: fetal heart rate detection for the health department.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. * Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in Email : westernsurgical@gmail.com Ph. : +91-281-2232871 / 2243159

IV. Equipment components: (fig. 1)

- 1. The gap for fixing the gallus
- 2. Number and symbol on LCD display interface Number:

The 5 beats average FHR value will display on this window.

• FETAL DOPPLER with FHR display Interface

*FETAL DOPPLER without FHR display interface




fig. 1. (Front view)

Due to constant upgradation design, price and features are subject to change any time without prior notice.



Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.

Symbol:

Power indicator or charge indicator



bpm or 161-210 bpm, the alarm indicator will appear.

Alarm for abnormal FHR During the range of 60-99



FHR beat display



5 beats average of FHR display.




fig. 2 (LCD window)



www.westernsurgical.in Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

© Copyright Reserved by : Western Surgical - Rajkot.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.
* Due to constant upgradation design, price and features are subject to change any time without prior notice.

3. Charge indicator:

Indicate the current intensity of the rechargeable battery.

The indicator is red while charging, and becomes green when the battery is full charged.

4. Working indicator:

The light is bright after turning on and become dark as it runs out of power.

5. Volume decrease button:

Click Volume button, the volume will decrease a grade Note: Long press 5 for more than two seconds, it will automatically switch to alarm switch

6. Increase the volume by switching click 6, the volume will increase a grade.

Note: Long press 6 for more than five seconds, it will automatically enter the "Test" interface. You shall press the turn off key to exit the interface.

7. Power switch:

Click the button to turn on, press the button for more than 2 seconds to turn off

Note: During the boot-up state, press this key to open / close the backlight function.

8. Probe

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.
* Due to constant upgradation design, price and features are subject to change any time without prior notice.



9. Charger jack: Connect the battery with the adapter.

10. Earphone jack:

11. Probe jack:

Connect the main frame with the probe

V. How to use this Doppler:

1. Take down / fix up the probe:

The correct way of taking out the probe from the jack is:




fig.3(Rear view)

Hold the unit with left hand, then take out the probe with the right hand from the probe jack (fig3). The installation of the probe is to held the unit with left hand, then put the probe with right hand in to the probe jack.

Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.

2. Turn on/off

Turn on the switch, the working indicator should be bright and the Doppler will start to work; the Doppler will stop working when the indicator becomes dark.

3. Look for the best detecting position:

Use gel to make sure the surface of the probe is in complete contact with the skin has. Adjust the volume controller to your desired level.

Notice: Also you can use earphones to detect the

FHR, you need to connect the earphone well first, and then search for the best position.

Attention:

- After use, please turn off the unit, wipe the coupling gel off the probe and fix the probe back to the probe jack.
- When the working indictor becomes dark or the sound is quiet, the Doppler needs to be recharged immediately.
- Do not drag the probe along the abdomen otherwise it will cause interference.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. * Due to constant upgradation design, price and features are subject to change any time without prior notice.



Each time pressing the decreasing key, the volume will reduce.

Each time pressing the volume increasing key, the

volume will increase till it reaches the maximum.

4. Volume controller adjust method:

5. Affirm the fetal heart:

FETAL DOPPLER:

immediately. The FHR data will be displayed automatically and will change as the baby's heart rate changes.

*FETAL DOPPLER: After hearing the fetal heart sound you can get the FHR by counting FHR, first for

instantly, please do not read the FHR value

6. Alarm switch setting

Western Surgical

of count depend on the doctor)

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.

This is FETAL DOPPLER specific feature. Long press the volume increase button 2 seconds, it will

15 seconds and times by 4 (the time and the method

Ph.: +91-281-2232871 / 2243159

© Copyright Reserved by: Western Surgical - Rajkot.

when FHR can be heard

When the fetal heart rate values are out of the range (120 ~ 160), the device will alarm. The icon 👨 will appear when the alarm is activated, press the button to turn on / off

7. Warning tone

the alarm function.

specific feature. This is

automatically activate this feature.

- No signal input within 1 minute, there will be a "drop" warning tone.
- No signal input within 3 minutes, there will be a "bit" tone. then the system will turn off automatically.

8. **Back light function**

This is specific feature. Boot - up state machine key switch is defined as the on / off backlight button. Backlight can be maintained for 15 seconds (that is, within 15 seconds when no signal is input or signal weak backlight will automatically shut down).

9. The cleanliness and disinfection after using:

Turn off the unit after using and clean off the gel on the probe, put the probe back to the jack to protect it.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. * Due to constant upgradation design, price and features are subject to change any time without prior notice.



When battery power is low, the sensitivity will decline, the working indicator, "" will go dark and FHR on the LCD will glint or not be digitally

*FETAL DOPPLER: Working indicator light will go dark

Notice: 75% alcohol can be used to clean and disinfect

the surface of the probe.

1. Low battery power:

FETAL DOPPLER:

displayed.

VI. How to maintain the unit

will be not clearly heard. 2. Charging method: Connect the AC adapter to the main power supply and then

and eventually fade out; the sensitivity will decline, the FHR

by connect to the Doppler unit. The charging indicator LCD will light normally. It needs about 8-12 hours charge again. **Note:** The first charge time should be 8 to 12 hours in order to extend battery life. The continuous charge time shall be

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.

no longer than 12 hours for normally use.

WESTERN SURGICAL



www.westernsurgical.in Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

3. Preservation method: Prevent Doppler from being destroyed by any liquid please

do not immerse the unit and probe in any liquid or water. Notice: If the Doppler outer shell is dirty after using,

please use the neuter cleanser to clean it, strictly prohibited to use any other organic materials to clean the unit including industry alcohol.

VII. Attention

- Caution: Before using, take the probe off and then turn on the Doppler. After using, first turn off the Doppler and then put probe back. Otherwise, there will be noise because of the reflection of ultrasound.
- Do not use telephone or cordless telephone within 10 meters while the unit is working, otherwise it cannot work normally.
- Charging time should be between 8-12 hours, except first charging between 12-16 hours. (more 12 hours),
- Turn off the unit after using to prolong the lifetime of the rechargeable battery.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.



If the device hasn't been used for three months, please charge it, otherwise, battery will be damaged
 Note: Under the guidance of doctor, detect fetal heart rate for pregnant women after 12 weeks' pregnancy.
 VIII. Shelf-life and Warranty

Use only the specified AC adapters and batteries

(supplied) for the unit. Others it may cause the risk of

Please use probe carefully as the probe is damaged

by customers which is not covered under the free

fire, electric shock or injury.

warranty.

2. Warranty:
The unit is backed by one-year limited warranty.
During the warranty period, which starts from

Precise electronic components are the main parts of the

Doppler; the host machine shelf-life is 3 years, except

Due to constant upgradation design, price and features are subject to change any time without prior notice.

www.westernsurgical.in

Email: westernsurgical@gmail

probe, battery and earphone (option).

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.



1. Shelf-life

service office to your residence. 3. Yearly safety check: The following safety check should be performed at least every 24 months by a qualified person who has adequate training, knowledge, and practical experience

the date of purchase, the defective parts will be

repaired free of charge. (excluding the probe and

optional earphone), Please note that you will be

charged for the cost of shipping the unit from

Inspect the safety relevant labels for legibility.

to perform these tests.

- Verify the device functions properly as described in the instructions for use.
- Inspect the unit and accessories for mechanical and functional damage, the data should be recorded in the operating manual. If the device can not work normally, it has to be repaired.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in

© Copyright Reserved by : Western Surgical - Rajkot.

IX. Trouble Shooting

1. Malfunction: While the unit is working normally, working indicator fails to light up/ no sound.

Possible cause:

- a. The rechargeable battery is going to be power off.
- b. Battery is damaged; c. The unit is damaged.

Solution:

- a. Recharge the unit;
- b. Contact the agent to change battery;
- c. Contact the agent to repair.
- 2. Malfunction: Connect the adapter and turn on the power switch, working indicator is not bright as well as charging indicator.

Possible cause :

- a. No AC power available;
- b. Adapter and unit are not properly connected;
- c. The adapter is damaged.

Solution:

a. Check AC power socket by qualified electrician;

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

- b. Make sure the connection between adapter and the unit is correct
- c . Contact the agent.
- 3. Malfunction: Working indicator is bright while the unit is working normally; but charging indicator is not bright, cannot be charged and several days later, the unit cannot work anymore.

Possible cause:

- a. No power available or adapter is damaged;
- b. Adapter cannot work normally or bad connection;
- c .Circuit of the adapter is damaged or charging indicator is not available;

Solution:

- Repair the power socket by qualified electrician;
- b. Contact the agent to repair it;
- c. Contact the agent to buy adapter or battery.
- 4. Malfunction: Turn on the power switch, working indicator becomes bright; but there's no sound while touching the surface of probe.

Possible cause:

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. * Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in
Email: westernsurgical@gmail.com

b. The rechargeable battery is nearly power off, faulty circuit:

a. Volume controller is adjusted too low to hear sound;

c. Probe is damaged; Solution:

- a. Release the volume controller;
- b. Charge the unit for 8 to 12 hours:
- c. Return the unit to the supplier for repair

5. Malfunction: Uncomfortable noise is heard while using it to detect FHR.

Possible cause:

- a. The rechargeable battery is near depletion of power.
- b. Not enough coupling gel between the probe and abdomen
- Noise occurs while dragging the probe on the abdomen
- d. Probe is damaged.

Solution:

- a. Recharge the unit;
- b. Ensure sufficient gel is used between the probe and abdomen

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.

c. Use gentle pressure on the abdomen to ensure well connection of the probe;

Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

d. Contact the agent to buy new probe.

6. Malfunction: Sensitivity is not sufficient.

Possible cause:

a. The rechargeable battery is going to be power off.

b. No sufficient coupling gel;

 c. Too much pressure is being applied to the pregnant woman's abdomen and muscles are not relaxed causing loud noise and interference

d. The probe is not located in the optimum position;

e. Sensitivity of probe declined.

Solution:

a. Recharge the unit;

 Ensure sufficient gel is used between the probe and abdomen;

c. Gentle press on the patient to ensure well connection of the probe and make patient relax;

d. Find the best position;

e. Contact the agent to replace the probe.

7. Malfunction: Digital is not stable while 500D+ is working.

Possible cause:

Western Surgical

Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.

Due to constant upgradation design, price and features are subject to change any time without prior notice.



www.westernsurgical.in Email : westernsurgical@gmail.com Ph. : +91-281-2232871 / 2243159

interference: b. Fault operation to connect the probe to the unit; c. There is an interference source in the local vicinity

a. While dragging the probe on the abdomen, there will be

within 10 m (e.g. high frequency electronic equipment, cell/mobile phone or cordless phones are working); d. The Doppler is damaged.

Solution:

- a. Determine optimum position and after about 5-10 seconds, it will get the accurate FHR; turn off the unit and turn on again;
- b. Ensure proper connection. c. The unit must be relocated away from the interference
- d. Contact the agent to repair.

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.



Email: westernsurgical@gmail.com Ph.: +91-281-2232871 / 2243159

www.westernsurgical.in

source;

Labels in the manual



★

TYPE BF APPLIED PART

CLASS II equipment





Environment:+5°C—+40°C



Waterproof



IPX4

Western Surgical

Up not more than 4 floors

Splash proof

In order to protect your right for repairing service, please take a few minutes to fill out the warranty card as below:

^{*} Carrying Warranty at Rajkot Office only on site warranty not provided free of cost. Due to constant upgradation design, price and features are subject to change any time without prior notice.



7.3 WARRANTY CERTIFICATE

western surgical product is warranted to be free from electrical and mechanical defects in material and workmanship, under normal use. The western surgical product must not have been moved from the site of original installation. A new or remanufactured part to replace the defective part will be provided without charge for the part itself, through an authorized western surgical service dealer. The replacement part assumes the unused portion of the warranty.

WESTERN SURGICAL WILL NOT BE RESPONSIBLE FOR:

- 1. Damage or repairs required as a consequence of faulty installation or application by others.
- 2. Damage or repairs needed as a consequence of any misapplication, negligent handling, improper servicing. unauthorized alteration, or improper operations.
- 3. Failure to start due to voltage conditions, blown fuses, open circuit breakers or other damages due to the inadequacy or interruption of electrical service.
- 4. Damage as a result of floods, winds, fires, lightning, accidents, corrosive atmosphere, or other conditions beyond the control of western surgical
- 5. Parts not supplied or designated by western surgical.

Date of Installation	Installed By		
Model No.	Serial No.		
Warranty Period			
Name of Doctor & Address :			

Customer Sign. With Stamps

Marketed By: Western Surgical Sign. With Stamps

No Claim Warranty:

- 1) Any Defect Througut Power Supply
- 2) Any Physical Damage
- 3) Under Warranty Standby Unit Not Provide
- 4) Under Warranty When Company Send Parts or Machine we Imidiat send to Buyer.

* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost.



www.westernsurgical.in Email: westernsuraical@amail.com Ph.: +91-281-2232871 / 2243159

OUR OTHER PRODUCTS RANGE



* Carrying Warranty at Rajkot Office only on site warranty not provided free of cost

WESTERN SURGICAL

Western Surgical

AN ISO 9001: 2008 & ISO 13485: 2015 AC 2012 CERTIFIED COMPANY

"Happy Home", 1st Floor, 23, Karanpara,

B/h. S.T. Bus Stand, Kanak Road,

Raikot-360 001. Ph.: +91 281-2232871/2243159 Mo.: +91 98250 69069 - +91 98250 45997

Email: westernsurgical@gmail.com

Email: info@westernsurgical.in

* www.westernsurgical.in *
© Copyright Reserved by : Western Surgical - Rajkot.

